

Technical Data Sheet

DAMPFIX SEAL 'N' FILLET



architectural +
structural
adhesives

DESCRIPTION

Dampfix Seal 'n' Fillet is a white, low modulus, polyurethane sealant which cures from moisture in the air to form a soft, elastic and weatherproof sealant.



FEATURES & BENEFITS

- High durability
- Excellent weather resistance
- Non-staining
- Fast cure

RECOMMENDED FOR

- Expansion and construction joints
- Brickwork and blockwork
- Wet areas

SURFACE PREPARATION

The surfaces to receive the **Dampfix Seal 'n' Fillet** must be clean and dry, be free from all oil, grease, dirt, water, old sealant and any protective coating. Roughen all non porous and plastic surfaces. If high bond strength is needed to the tile then porous substrates must be primed using **Bostik N49 Primer** and non porous substrates primed with **Bostik N40 Primer**.

APPLICATION

Place **Dampfix Seal 'n' Fillet** sausage into an appropriate barrel gun and clip the end of the sausage. Screw the top of the nozzle and housing onto the barrel gun. Cut off nozzle at tip at 45° angle to desired thickness. Apply **Dampfix Seal 'n' Fillet** in a continuous operation using a firm pressure on the trigger of the gun to properly fill and seal the cavity.

CLEAN UP

Clean tools and equipment with **Bostik Handi-Clean Wipes** while the sealant is still wet.

PACKAGING

600ml (720g) sausages

COVERAGE

600ml sausage: 3mm bead 81 metres
6mm bead 19 metres
20mm bead 4.4 metres

SAFETY PRECAUTIONS

Uncured sealant will cause irritation. Gloves and protective goggles must be worn during application of **Dampfix Seal 'n' Fillet**. Avoid contact with skin and eyes and avoid breathing vapour. If swallowed, do not induce vomiting. Give a glass of water. If poisoning occurs, contact a physician. If skin contact occurs, remove contaminated clothing and wash skin thoroughly for a minimum of 15 minutes. If irritation persists, consult a physician. It is advisable to avoid personal contact and use good occupational health and safety practices. For more detailed information refer to product MSDS.

SHELF LIFE

Unopened sausages can be stored for up to 12 months in a cool, dry and weatherproof environment.

LIMITATIONS

- Do not apply in temperatures below 5°C
- Do not use in swimming pools or spas

Technical Data Sheet

DAMPFIX SEAL 'N' FILLET



architectural +
structural
adhesives

TECHNICAL SERVICES TOLL FREE NUMBER
1800 813 890 Australia
0508 222 272 New Zealand (land lines only)
or visit www.asaltd.com.au
a member of the Bostik group of companies



GUARANTEE

ASA guarantees this product for 10 years provided application is in accordance with manufacturer's directions and the Australian Standards for Waterproofing. ASA's liability is limited to the cost of replacing effected ASA product only. ASA reserves the right to inspect. Contact ASA for full guarantee terms.

NSW HEAD OFFICE	VIC	QLD	SA	WA	NZ
Ph: (02) 9725 4666 Fax: (02) 9725 4427	Ph: (03) 9331 6888 Fax: (03) 9331 6222	Ph: (07) 3260 2422 Fax: (07) 3260 2411	Ph: (08) 8244 2853 Fax: (08) 8244 0522	Ph: (08) 9314 5200 Fax: (08) 9337 4377	Ph: +64 9270 3168 Fax: +64 9270 6170