

Technical Data Sheet

GROUT SEALER



architectural +
structural
adhesives

DESCRIPTION

Grout Sealer is a water based silicone grout sealer designed to make grout water repellent. **Grout Sealer** coats the pores of the grout and renders them impermeable to water.

FEATURES & BENEFITS

- Water-based
- Easy application
- Less penetration of water through grout joint
- Grout easier to keep clean

RECOMMENDED FOR

- Cement based wall grout
- Cement based floor grout



SURFACE PREPARATION

Ensure the surface of the grout is clean, dry and free from grease, oil, wax, dirt, dust and any other contaminants.

APPLICATION

Spray **Grout Sealer** on grout surface ensuring the grout is fully saturated. After approximately 5 minutes, wipe excess from the surface with a clean, damp cloth. Allow grout joint to dry.

CLEAN UP

Clean up excess sealer with a damp cloth.

PACKAGING

750ml plastic spray bottle.

COVERAGE

750ml **Grout Sealer** is sufficient for approximately 20m² grouting.

SAFETY PRECAUTIONS

Avoid contact with skin and eyes. Wear protective gloves when applying product. If contact with eyes occurs, flush with copious amounts of water ensuring eyes are irrigated for at least 15 minutes. If ingested, do not induce vomiting. Give plenty of water to drink. Consult physician. For more detailed information refer to product MSDS.

SHELF LIFE

Unopened containers can be stored for up to 12 months in a cool, dry and weatherproof environment.

LIMITATIONS

- Do not use on wet surfaces
- Not suitable for use with marble, granite or limestone tiles
- Do not use on porous tiles

TECHNICAL SERVICES TOLL FREE NUMBER

1800 813 890 Australia

0508 222 272 New Zealand (land lines only)

or visit www.asaltd.com.au

a member of the Bostik group of companies



NSW HEAD OFFICE	VIC	QLD	SA	WA	NZ
Ph: (02) 9725 4666 Fax: (02) 9725 4427	Ph: (03) 9331 6888 Fax: (03) 9331 6222	Ph: (07) 3260 2422 Fax: (07) 3260 2411	Ph: (08) 8244 2853 Fax: (08) 8244 0522	Ph: (08) 9314 5200 Fax: (08) 9337 4377	Ph: +64 9270 3168 Fax: +64 9270 6170