



technical data sheet

BOSTIK FINE FINISH

DESCRIPTION

Bostik Fine Finish is a ready to use surface finish suitable for covering slight imperfections in timber, plaster, mortar, concrete and primed metal, providing a hard and smooth finish. It has been specially designed for use as a surface finish under gloss paint.

TYPICAL TECHNICAL DATA

Type:	Water-based paste
Colour:	White
Shelf life:	12 months

PACKAGING

Available in 630gm and 1.22kg containers

PREPARATION

Surfaces should be clean and dry with no loose or powdery material or paint. If applying over gloss paint, use Bostik Degloss to improve adhesion.

APPLICATION

- Knead tube before use to ensure an even consistency.
- Squeeze a small amount of filler onto a flexible filling blade.
- Apply in thin coats (1-2mm) to avoid cracking, pressing firmly into the area being filled. Remove any excess filler.
- Allow each layer to dry before applying next layer. Dries in 2-3 hours in thin applications depending on atmospheric conditions.
- When dry, use 180-240 grit sandpaper id a smoother surface if required.
- It is not necessary to prime over Bostik Fine Finish before painting.

- Bostik Fine Finish can be painted with water or oil based paints.

PRECAUTION

Not suitable for outdoor use, or filling large holes – use Bostik Heavy Filler instead. Use Bostik Fill-A-Gap sealant where movement occurs

P.A.T.S (Pretested Adhesion To Substrate) Programme

Bostik offer a service in which a program has been established to eliminate potential field problems by pre-testing Bostik adhesives with samples of building materials to which the adhesive will be applied. This service is available on large projects where pre-application testing will aid in determining the proper surface preparation method to achieve optimum adhesion. Consult a Bostik representative for further information.

HEALTH AND SAFETY

A Material Safety Data Sheet is available on request. Bostik Fine Finish is non-toxic and non-hazardous

CLEAN-UP

Clean tools and hands with soapy water.

STORAGE

12 months in unopened container. Close lid tightly after use. Store in a cool place out of direct sunlight

BOSTIK FINE FINISH

ITEM NO.	STOCK SIZE
251801	FINE FINISH 630GM
251828	FINE FINISH 1.22KG

The representations and recommendations regarding the products are based on tests which we believe to be reliable. However, no guarantee of their accuracy can be made because of the great range of field conditions and variations encountered in raw materials, manufacturing equipment and methods. Thus, the products are sold with a limited warranty only, and on the condition that purchasers will make their own tests to determine the suitability of the product for their particular purposes. Under no circumstances will Bostik Australia Pty Ltd be liable to anyone except for replacement of the products or refund of the purchase price.

ALL SALES ARE EXPRESSLY LIMITED TO THE TERMS AND CONDITIONS OF SALE OF BOSTIK AUSTRALIA PTY LTD



BOSTIK AUSTRALIA PTY LTD
Phone: +61-3-9279 9333
Fax: +61-3-9279 9240

SYDNEY
Phone: 02 8825 3488
Fax: 02 8825 3411

BOSTIK NZ LIMITED
Phone: +64-4-567 5119
Fax: +64-4-567-5412

ADELAIDE
Phone: 08 8244 0511
Fax: 08 8244 0522

BOSTIK SINGAPORE PTE LTD
Phone: +65-6863 4088
Fax: +65-6863 4077

PERTH
Phone: 08 9258 6218
Fax: 08 9258 7687

BOSTIK (MALAYSIA) SDN BHD
Phone: +606 764 3246
Fax: +606 764 3248

BRISBANE
Phone: 07 3260 2206
Fax: 07 3260 2123

(ABN 79 003 893 838)

Product:	Bostik Fine Finish
Issue Date:	September 2001
Issue No:	1
Division:	Hardware
Total Pages:	1

FOR FURTHER INFORMATION