

BOSTIK CONTACT GRIP

Fix It Once

DESCRIPTION

Bostik Contact Grip is a solvent based, high solids contact adhesive. It is primarily used in the furniture and allied industries for fixing plastic laminates and rigid or flexible decorative surface coverings to wood, MDF, particle board, plywood, leather and metal.

Bostik Contact Grip also provides excellent adhesion to most natural and neoprene rubbers as well as a wide variety of porous and non-porous surfaces.

FEATURES & BENEFITS

- n-Hexane formula
- Safe quick drying
- Heat resistant

TYPICAL TECHNICAL DATA

Type:	Polychloroprene rubber / resin
Colour:	Pale yellow
Solvent:	Aliphatic / Aromatic hydrocarbon and ketone mixture
Viscosity:	Medium syrup
Solids:	approx. 22%
S.G.:	approx. 0.83
Flash Point:	Less than 0°C
Heat Resistance:	>150°C (Tested to AS 2131:1978)

PACKAGING

55 ml tube.

COVERAGE:

For a fix it once job.

PREPARATION

Prior to application ensure all surfaces are clean, dry and free of oil and grease.

APPLICATION INSTRUCTIONS

Apply **Bostik Contact Grip** to both surfaces evenly. Allow surfaces to dry for approximately 10-15 minutes (depending on weather conditions). Align the surfaces accurately, then join surfaces.

The representations and recommendations regarding the products are based on tests which we believe to be reliable. However, no guarantee of their accuracy can be made because of the great range of field conditions and variations encountered in raw materials, manufacturing equipment and methods. Thus, the products are sold with a limited warranty only, and on the condition that purchasers will make their own tests to determine the suitability of the product for their particular purposes. Under no circumstances will Bostik Australia Pty Ltd be liable to anyone except for replacement of the products or refund of the purchase price.

ALL SALES ARE EXPRESSLY LIMITED TO THE TERMS AND CONDITIONS OF SALE OF BOSTIK AUSTRALIA PTY LTD

PRECAUTION

Do not use on copper, expanded polystyrene foam, unbacked PVC or untreated polyethylene or polypropylene plastics. Not recommended for exterior use. If unsure, please consult Bostik for correct recommendation and advice.

HEALTH AND SAFETY

Gloves and protective goggles must be worn during application and use.

- Avoid contact with skin, eyes and avoid breathing in vapour.
- Wear protective gloves when mixing or using
- If poisoning occurs, contact a doctor or Poisons Information Centre.
- If skin contact occurs, remove contaminated clothing and wash skin thoroughly for a minimum of 15 minutes and see a doctor.
- For more detailed information refer to Material Safety Data Sheet.

CLEAN-UP

Clean up with **Bostik 9913 Solvent** or mineral turps. Thinning is not recommended. Equipment must be thoroughly cleaned at the end of each day to ensure satisfactory and uninterrupted working.

STORAGE

Minimum of 12 months from date of manufacture if stored under cover between 5°C and 30°C. Store away from heat sources and naked flames, under cover and well ventilated.

FIRE

The solvents are highly flammable.

BOSTIK CONTACT BOND

Item No	Stock Size	Units/Ctn
298611	Contact Grip 55ml	6
289523	Contact Grip 5ml	30

FOR FURTHER INFORMATION



BOSTIK AUSTRALIA PTY LTD
Phone: +61-3-9279 9333
Fax: +61-3-9279 9240

BOSTIK NZ LIMITED
Phone: +64-4-567 5119
Fax: +64-4-567-5412

BOSTIK SINGAPORE PTE LTD
Phone: +65-6863 4088
Fax: +65-6863 4077

BOSTIK (MALAYSIA) SDN BHD
Phone: +606 764 3246
Fax: +606 764 3248

SYDNEY
Phone: 02 8825 3488
Fax: 02 8825 3411

ADELAIDE
Phone: 08 8244 0511
Fax: 08 8244 0522

PERTH
Phone: 08 9258 6218
Fax: 08 9258 7687

BRISBANE
Phone: 07 3260 2206
Fax: 07 3260 2123

(ABN 79 003 893 838)

Product: Bostik Fix It Once
Contact Grip 55ml
Issue Date: September 2007
Issue No: 3
Division: Hardware
Total Pages: 1