



## technical data sheet

# BOSTIK FLEXIBLE FILLER

### PRODUCT

Bostik Flexible Gap Filler is a strong, super flexible (20%), anti-fungal, mildew resistant acrylic gap filler. Flexible Filler is designed for internal and external applications where a flexible joint sealant is required.

### DESCRIPTION

Bostik Flexible Filler offers superior adhesion properties when cured and is more flexible than conventional fillers. Bostik Flexible Filler can be painted over with most types of paint, and provides excellent adhesion to plasterboard, wood, brick, concrete, cement sheet and ceramic tiles.

### RECOMMENDED USES

- Bathroom, kitchen and laundry.
- Sealing gaps in plasterboard, brickwork, timber, concrete, cement sheet and ceramic tiles.
- May be painted with conventional available paints.
- Window and door perimeter sealing

### FEATURES & BENEFITS

- Anti-fungal
- Good adhesion to most building materials
- May be overpainted
- Excellent flexible properties
- Water based technology, water clean up
- Non slump
- Interior/exterior
- Australian made

### TYPICAL PROPERTIES

Appearance	Smooth, paste like consistency
Colour	White
Chemical Type	Water based acrylic
Specific Gravity	1.5
Service Temperature	-20°C to +75°C
Tack Free Working Time	15mins @ 20°C
Total Max Joint Movement	Up To 20%
Max Joint Width	25mm.

Results are after seven days cure @ 25°C and 50%RH.

### APPLICATION INSTRUCTIONS:

Cut tip off cartridge. Cut nozzle to desired size at 45° angle. Screw nozzle onto cartridge. Place cartridge into caulking gun. Hold gun at 45° angle with nozzle in contact with both sides of joint. Apply by pushing sealant ahead of the nozzle, thus ensuring filler is pushed firmly into place. Remove excess filler with a wet putty knife or damp cloth. Becomes touch dry within 30 minutes under ambient conditions.

For best results when painting allow 72 hours prior to painting (allow longer curing time in cool or damp conditions).

### PRECAUTIONS

Not recommended for use

- Where abrasion or physical abuse can be expected.
- In sealing submerged joints
- Underwater or in marine applications
- When applied to substrates below 5°C
- With absorptive surfaces such as marble, limestone or granite without prior testing for staining and/or discolouration.
- On powder coated surfaces
- On damp substrates
- On trafficable applications.
- Where joint movement is excessive
- Where exposed to water or where water pools.

### P.A.T.S (Pretested Adhesion To Substrate) Programme

Bostik offer a service in which a program has been established to eliminate potential field problems by pre-testing Bostik adhesives with samples of building materials to which the adhesive will be applied. This service is available on large projects where pre-application testing will aid in determining the proper surface preparation method to achieve optimum adhesion. Consult a Bostik representative for further information.

### SAFETY DIRECTIONS

- Avoid contact with skin and eyes. If contact occurs, wash area with large quantities of water. Wear gloves for prolonged or repeated exposure.
- For more detailed information refer to Material Safety Data Sheet.

### CLEAN-UP

Clean up uncured material and equipment with water immediately after using. For removal on skin, uncured sealant can be removed with Bostik Handi-Clean towels.

### PACKAGING

Bostik Flexible Filler is available in 440gm cartridges in cartons of 20.

Item No	Stock Size	Bar Code
275360	20 x 410 g cartridges	9310492441009

*The representations and recommendations regarding the products are based on tests which we believe to be reliable. However, no guarantee of their accuracy can be made because of the great range of field conditions and variations encountered in raw materials, manufacturing equipment and methods. Thus, the products are sold with a limited warranty only, and on the condition that purchasers will make their own tests to determine the suitability of the product for their particular purposes. Under no circumstances will Bostik Findley Australia Pty Ltd be liable to anyone except for replacement of the products or refund of the purchase price.*

ALL SALES ARE EXPRESSLY LIMITED TO THE TERMS AND CONDITIONS OF SALE OF BOSTIK FINDLEY AUSTRALIA PTY LTD

### FOR FURTHER INFORMATION

**BOSTIK FINDLEY AUSTRALIA PTY LTD**  
Phone: +61-3-9279 9333  
Fax: +61-3-9279 9240

**BOSTIK FINDLEY NZ LIMITED**  
Phone: +64-4-567 5119  
Fax: +64-4-567-5412

**BOSTIK FINDLEY SINGAPORE PTE LTD**  
Phone: +65-6863 4088  
Fax: +65-6863 4077

**BOSTIK FINDLEY (MALAYSIA) SDN BHD**  
Phone: +606 764 3246  
Fax: +606 764 3248

**SYDNEY**  
Phone: 02 8825 3488  
Fax: 02 8825 3411

**ADELAIDE**  
Phone: 08 8244 0511  
Fax: 08 8244 0522

**PERTH**  
Phone: 08 9258 6218  
Fax: 08 9258 7687

**BRISBANE**  
Phone: 07 3260 2206  
Fax: 07 3260 2123

**(ABN 79 003 893 838)**

Product:	Bostik Flexible Filler
Issue Date:	May 2004
Issue No:	1
Division:	Hardware
Total Pages:	1

