



technical data sheet

BOSTIK HEAVY FILLER

DESCRIPTION

Bostik Heavy Filler is a ready to use filler suitable for all large patching jobs either indoors or outdoors. It adheres well to mortar, concrete, timber, plaster and primed metal.

RECOMMENDED USES

- Use on mortar, concrete, timber, plaster, and primed metal.
- Ideal for patching large cracks and holes.

FEATURES & BENEFITS

- Ready to use filler for interior and exterior applications.
- Can be sanded, if a smooth finish is required.

PERFORMANCE PROPERTIES

Type:	Exterior-grade paste
Colour:	Grey
Shelf life:	12 months

PACKAGING

Available in 330gm, 600gm and 1.75kg containers

PREPARATION

Surfaces should be clean and dry with no loose or powdery material or paint. Prime exterior surfaces appropriately before application.

APPLICATION INSTRUCTIONS

- Knead tube before use to ensure an even consistency.
- Squeeze a small amount of filler onto a flexible filling blade.
- Apply in thin layers pressing firmly into the area being filled. Remove any excess filler.
- Dries in 2-3 hours in thin applications, or 5-6 hours in deep cracks depending on atmospheric conditions.
- Sand with 120-180 grit sandpaper if a smooth finish is required.
- It is not necessary to prime before painting.

- Bostik Heavy Filler can be painted over with water or oil-based paints.

PRECAUTIONS

- Use Bostik Fill-A-Gap sealant where movement occurs.
- If filling very large holes, use an appropriate bridging material before filling.

P.A.T.S (Pretested Adhesion To Substrate) Programme

Bostik offer a service in which a program has been established to eliminate potential field problems by pre-testing Bostik adhesives with samples of building materials to which the adhesive will be applied. This service is available on large projects where pre-application testing will aid in determining the proper surface preparation method to achieve optimum adhesion. Consult a Bostik representative for further information.

HEALTH AND SAFETY

A Material Safety Data Sheet is available on request. Bostik Heavy Filler is non-toxic and non-hazardous

CLEAN-UP

Clean tools and hands with soapy water.

STORAGE

- 12 months in unopened container
- Close lid tightly after use
- Store in a cool place out of direct sunlight

BOSTIK HEAVY FILLER

ITEM NO.	STOCK SIZE	
251763	HEAVY FILLER	330GM
251771	HEAVY FILLER	600GM
251798	HEAVY FILLER	1.75KG

The representations and recommendations regarding the products are based on tests which we believe to be reliable. However, no guarantee of their accuracy can be made because of the great range of field conditions and variations encountered in raw materials, manufacturing equipment and methods. Thus, the products are sold with a limited warranty only, and on the condition that purchasers will make their own tests to determine the suitability of the product for their particular purposes. Under no circumstances will Bostik Findley Australia Pty Ltd be liable to anyone except for replacement of the products or refund of the purchase price.

ALL SALES ARE EXPRESSLY LIMITED TO THE TERMS AND CONDITIONS OF SALE OF BOSTIK AUSTRALIA PTY LTD



BOSTIK AUSTRALIA PTY LTD
 Phone: +61-3-9279 9333
 Fax: +61-3-9279 9240

SYDNEY
 Phone: 02 8825 3488
 Fax: 02 8825 3411

BOSTIK NZ LIMITED
 Phone: +64-4-567 5119
 Fax: +64-4-567-5412

ADELAIDE
 Phone: 08 8244 0511
 Fax: 08 8244 0522

BOSTIK SINGAPORE PTE LTD
 Phone: +65-6863 4088
 Fax: +65-6863 4077

PERTH
 Phone: 08 9258 6218
 Fax: 08 9258 7687

BOSTIK (MALAYSIA) SDN BHD
 Phone: +606 764 3246
 Fax: +606 764 3248

BRISBANE
 Phone: 07 3260 2206
 Fax: 07 3260 2123

(ABN 79 003 893 838)

FOR FURTHER INFORMATION

Product:	Bostik Heavy Filler
Issue Date:	September 2001
Issue No:	1
Division:	Hardware
Total Pages:	1