



technical data sheet

BOSTIK INTERIOR TIMBER FILLER

DESCRIPTION

Bostik Interior Timber Filler is a ready to use filler suitable for filling holes and cracks in interior joinery and doors. It is also suitable as a grain and edge filler where a smooth finish is required. Once sanded, it can be tinted, stained or painted.

RECOMMENDED USES

- Ideal for filling holes, cracks, dents, chips in timber.
- For grain and edge filling.
- Use on interior joinery and doors.
- Can be tinted, stained or painted.

TYPICAL TECHNICAL DATA

Type:	Water-based paste
Colour:	Beige

PACKAGING

Available in 470gm and 935gm containers

PREPARATION

Surfaces should be clean and dry with no loose or powdery material or paint.

APPLICATION

- Knead tube before use to ensure an even consistency.
- Squeeze a small amount of filler onto a flexible filling blade.
- Apply in thin layers pressing firmly into the area being filled. Remove any excess filler.
- Allow each layer to dry before applying next layer. Dries in 2-3 hours in thin applications depending on atmospheric conditions.
- When dry, use 120-180 grit sandpaper to smooth surface.

- It is not necessary to prime over Bostik Interior Timber Filler before varnishing, staining or painting.
- Bostik Interior Timber Filler can be painted with water or oil based paints.
- When using tints and stains, the final application of clear varnish will deepen the colour of Bostik Interior Filler.

P.A.T.S (Pretested Adhesion To Substrate) Programme

Bostik offer a service in which a program has been established to eliminate potential field problems by pre-testing Bostik adhesives with samples of building materials to which the adhesive will be applied. This service is available on large projects where pre-application testing will aid in determining the proper surface preparation method to achieve optimum adhesion. Consult a Bostik representative for further information.

HEALTH AND SAFETY

A Material Safety Data Sheet is available on request. Bostik Interior Timber Filler is non-toxic and non-hazardous

CLEAN-UP

Clean tools and hands with soapy water.

STORAGE

12 months in unopened container
Close lid tightly after use
Store in a cool place out of direct sunlight

BOSTIK INTERIOR TIMBER FILLER

ITEM NO.	STOCK SIZE
251747	INTERIOR TIMBER FILLER 470GM
251755	INTERIOR TIMBER FILLER 935GM

The representations and recommendations regarding the products are based on tests which we believe to be reliable. However, no guarantee of their accuracy can be made because of the great range of field conditions and variations encountered in raw materials, manufacturing equipment and methods. Thus, the products are sold with a limited warranty only, and on the condition that purchasers will make their own tests to determine the suitability of the product for their particular purposes. Under no circumstances will Bostik Australia Pty Ltd be liable to anyone except for replacement of the products or refund of the purchase price.

ALL SALES ARE EXPRESSLY LIMITED TO THE TERMS AND CONDITIONS OF SALE OF BOSTIK AUSTRALIA PTY LTD

FOR FURTHER INFORMATION

**BOSTIK
AUSTRALIA PTY LTD**
Phone: +61-3-9279 9333
Fax: +61-3-9279 9240

**BOSTIK
NZ LIMITED**
Phone: +64-4-567 5119
Fax: +64-4-567-5412

**BOSTIK
SINGAPORE PTE LTD**
Phone: +65-6863 4088
Fax: +65-6863 4077

**BOSTIK
(MALAYSIA) SDN BHD**
Phone: +606 764 3246
Fax: +606 764 3248

SYDNEY
Phone: 02 8825 3488
Fax: 02 8825 3411

ADELAIDE
Phone: 08 8244 0511
Fax: 08 8244 0522

PERTH
Phone: 08 9258 6218
Fax: 08 9258 7687

BRISBANE
Phone: 07 3260 2206
Fax: 07 3260 2123

(ABN 79 003 893 838)

Product: Bostik Interior Timber Filler
Issue Date: September 2001
Issue No: 1
Division: Hardware
Total Pages: 1

