



## technical data sheet

# BOSTIK KWIK-SET

## Light Weight Filler

### PRODUCT

Bostik Kwik-Set light weight filler is a ready to use repair paste, suitable for filling interior cracks, chips and holes in plaster, plasterboard, wallboard and wood.

### RECOMMENDED USES

- Use on mortar, concrete, timber, plaster, and primed metal.
- Suitable for repairs to plaster and plasterboard.

### FEATURES & BENEFITS

- Paintable in 30 minutes
- Ready to use
- Applicator included

### PERFORMANCE PROPERTIES

Type	Water based acrylic
Colour	White
Shelf Life	12 months (in sealed container)
PH	7-9
Density	Approximately 0.5g/cm <sup>3</sup>
Solids	High

### PACKAGING

Available in 350ml and 750ml container with applicator.

### PREPARATION

Surfaces should be clean and dry with no loose or powdery material or paint.

### APPLICATION INSTRUCTIONS

- Prime any exposed nail heads prior to use
- Using applicator provided, apply Kwik-Set to required area pressing firmly into hole-crack.
- Smooth off area and allow to dry for 30 minutes in thin areas, allow a longer time period for deeper holes/cracks and on non – porous surfaces

*The representations and recommendations regarding the products are based on tests which we believe to be reliable. However, no guarantee of their accuracy can be made because of the great range of field conditions and variations encountered in raw materials, manufacturing equipment and methods. Thus, the products are sold with a limited warranty only, and on the condition that purchasers will make their own tests to determine the suitability of the product for their particular purposes. Under no circumstances will Bostik Australia Pty Ltd be liable to anyone except for replacement of the products or refund of the purchase price.*

**ALL SALES ARE EXPRESSLY LIMITED TO THE TERMS AND CONDITIONS OF SALE OF BOSTIK AUSTRALIA PTY LTD**

- Kwik-Set can be sanded and painted when dry (allow 24 hours drying time before using an oil based paint).

### PRECAUTION

- Not suitable for outdoor use
- Use Bostik Flexible Filler where joint movement occurs

### P.A.T.S (Pretested Adhesion To Substrate) Programme

Bostik offer a service in which a program has been established to eliminate potential field problems by pre-testing Bostik adhesives with samples of building materials to which the adhesive will be applied. This service is available on large projects where pre-application testing will aid in determining the proper surface preparation method to achieve optimum adhesion. Consult a Bostik representative for further information.

### HEALTH AND SAFETY

A Material Safety Data Sheet is available on request. Bostik Kwik-Set is non-toxic and non-hazardous

### CLEAN-UP

Clean tools and hands with soapy water while still wet.

### STORAGE

12 months in unopened container.

Close lid tightly after use.

Store in a cool place out of direct sunlight.

If product appears to dry stir in 1 teaspoon of water with applicator.

Item No	STOCK SIZE
308781	Bostik Kwik-Set Light Weight Filler 160 gm
308773	Bostik Kwik-Set Light Weight Filler 300 gm



**BOSTIK AUSTRALIA PTY LTD**  
 Phone: +61-3-9279 9333  
 Fax: +61-3-9279 9240

**SYDNEY**  
 Phone: 02 8825 3488  
 Fax: 02 8825 3411

#### FOR FURTHER INFORMATION

**BOSTIK NZ LIMITED**  
 Phone: +64-4-567 5119  
 Fax: +64-4-567-5412

**ADELAIDE**  
 Phone: 08 8244 0511  
 Fax: 08 8244 0522

**PERTH**  
 Phone: 08 9258 6218  
 Fax: 08 9258 7687

(ABN 79 003 893 838)

**BOSTIK SINGAPORE PTE LTD**  
 Phone: +65-6863 4088  
 Fax: +65-6863 4077

**BRISBANE**  
 Phone: 07 3260 2206  
 Fax: 07 3260 2123

**BOSTIK (MALAYSIA) SDN BHD**  
 Phone: +606 764 3246  
 Fax: +606 764 3248

Product:	Bostik Kwik-Set Light Weight Filler
Issue Date:	July 2005
Issue No:	1
Division:	Hardware