



technical data sheet

Bostik Light Filler

DESCRIPTION

Bostik Light Filler is a ready to use fine particle filler suitable for filling small cracks and chips on plaster and plasterboard. Sand lightly for an excellent base for painting.

FEATURES & BENEFITS

- Ready to use fine surface filler.
- Ideal for filling small cracks and chips.
- Suitable for repairs to plaster and plasterboard.
- Excellent base for painting.

TYPICAL TECHNICAL DATA

Type:	Plaster paste
Colour:	White
Shelf life:	12 months

PACKAGING

Available in 550gm, 1.13kg and 3.4kg containers

PREPARATION

Surfaces should be clean and dry with no loose or powdery material or paint.

APPLICATION INSTRUCTIONS

- Knead tube before use to ensure an even consistency.
- Squeeze a small amount of filler onto a flexible filling blade.
- Apply thin layers pressing firmly into the area being filled. Remove any excess filler.
- Allow each layer to dry before applying next layer. Bostik Light Filler dries in 2-3 hours in thin applications depending on atmospheric conditions.
- When dry, sand lightly with 120-180 grit sandpaper for an excellent base for painting.
- It is not necessary to prime before painting.

- Bostik Light Filler can be painted over with water or oil based paints.

PRECAUTION

Not suitable for outdoor use, or filling large holes – use Bostik Heavy Filler instead.

P.A.T.S (Pretested Adhesion To Substrate) Programme

Bostik offer a service in which a program has been established to eliminate potential field problems by pre-testing Bostik adhesives with samples of building materials to which the adhesive will be applied. This service is available on large projects where pre-application testing will aid in determining the proper surface preparation method to achieve optimum adhesion. Consult a Bostik representative for further information.

HEALTH AND SAFETY

A Material Safety Data Sheet is available on request. Bostik Light Filler is non-toxic and non-hazardous

CLEAN-UP

Clean tools and hands with soapy water.

STORAGE

12 months in unopened container
Close lid tightly after use
Store in a cool place out of direct sunlight

BOSTIK LIGHT FILLER

ITEM NO.	STOCK SIZE	
251933	LIGHT FILLER	3.4KG
251917	LIGHT FILLER	550GM
251925	LIGHT FILLER	1.13KG

The representations and recommendations regarding the products are based on tests which we believe to be reliable. However, no guarantee of their accuracy can be made because of the great range of field conditions and variations encountered in raw materials, manufacturing equipment and methods. Thus, the products are sold with a limited warranty only, and on the condition that purchasers will make their own tests to determine the suitability of the product for their particular purposes. Under no circumstances will Bostik Australia Pty Ltd be liable to anyone except for replacement of the products or refund of the purchase price.

ALL SALES ARE EXPRESSLY LIMITED TO THE TERMS AND CONDITIONS OF SALE OF BOSTIK AUSTRALIA PTY LTD



BOSTIK
AUSTRALIA PTY LTD
Phone: +61-3-9279 9333
Fax: +61-3-9279 9240

SYDNEY
Phone: 02 8825 3488
Fax: 02 8825 3411

BOSTIK
NZ LIMITED
Phone: +64-4-567 5119
Fax: +64-4-567-5412

ADELAIDE
Phone: 08 8244 0511
Fax: 08 8244 0522

FOR FURTHER INFORMATION

BOSTIK
SINGAPORE PTE LTD
Phone: +65-6863 4088
Fax: +65-6863 4077

PERTH
Phone: 08 9258 6218
Fax: 08 9258 7687

(ABN 79 003 893 838)

BOSTIK
(MALAYSIA) SDN BHD
Phone: +606 764 3246
Fax: +606 764 3248

BRISBANE
Phone: 07 3260 2206
Fax: 07 3260 2123

Product:	Bostik Light Filler
Issue Date:	September 2001
Issue No:	1
Division:	Hardware
Total Pages:	1