


# Dribond Colour Seal

**A TOUGH FLEXIBLE SILICONISED WATER-RESISTANT SEALANT**

**PACKAGING**




**MIXING**



**APPLICATION**



**USES**



**SUBSTRATES**

POROUS SURFACES  
CERAMIC TILES  
BRICK  
BLOCK  
CONCRETE  
BATHS, BASINS  
BUILDER BOARDS  
EXPANSION CONTROL  
JOINT IN LOW RISE  
CONSTRUCTION

**DESCRIPTION**

COLOUR SEAL is a tough, siliconised, flexible, durable water based sealant that is easily applied and pointed.

**USES**

An internal and external sealant for bathrooms and tiled areas and medium performance vertical control joints.

**FEATURES**

- Mould and UV light resistant.
- Can be applied to damp surfaces.
- Water based.

**COVERAGE** (Approximate)

5mm x 5mm joints – 12m/cartridge. 10mm x 10mm joints – 3.5m/cartridge.

**COLOURS**

White, Sandstone, Ivory, Light Grey, Mid Grey, Beige, Tan, Black.

**PERFORMANCE DATA**

Tensile Strength (ASTM 0412)	0.522 N/mm <sup>2</sup>
Elongation (ASTM 0412)	205%

**SPECIFICATION**

The sealant shall be a water based acrylic and have a minimum performance of 205% Elongation and a Tensile Strength of 0.52 N/mm<sup>2</sup> such as COLOUR SEAL manufactured by Construction Chemicals and shall be applied in accordance with the manufacturer's applications instructions.

**JOINT PREPARATION**

The surface to be sealed must be sound, clean, free of all contaminants and water.

**APPLICATION**

Cut the nozzle tip to the desired diameter and cut the seal on the cartridge.

Gun the sealant bead with a steady pressure. Push the sealant ahead of the nozzle to force the sealant into the joint and smooth the bead at the same time.

The surface can be smoothed with a wet knife, scraper or finger for up to 5 minutes after application. For best performance the sealant depth should be half the width.

**CURING**

Full cure occurs in 2-7 days depending on bead size, temperatures and humidity. Protect from moisture for 24 hours after application.

**CLEANING**

Remove uncured sealant with a wet cloth and cured mastic with a blade or knife.

**LIMITATIONS:**

DO NOT APPLY in immersed application or when temperatures are below 5°C or sections greater than 10mm x 10mm.

**SHELF LIFE**

2 years



- **ADELAIDE** 467 - 469 SOUTH RD REGENCY PARK 5010 PH: (08) 8346 8013 FAX: (08) 8340 2052
- **BRISBANE** 45 COULSON ST WACOL 4076 PH: (07) 3271 2944 FAX: (07) 3271 3892
- **MELBOURNE** 11 GABRIELLE CT BAYSWATER NORTH 3153 PH: (03) 9761 4711 FAX: (03) 9761 4748
- **PERTH** 11 COLLIE RD WELSHPOOL 6106 PH: (08) 9356 9999 FAX: (08) 9356 9955
- **SYDNEY** 31 NEWTON RD WETHERILL PARK 2164 PH: (02) 9756 3533 FAX: (02) 9756 3534
- **AUCKLAND** 16 CARPENTER RD EAST TAMAKI PH: (09) 273 5444 FAX: 0800 266 236
- **KUALA LUMPUR** LOT 2 JALAN KECAPI 33/2 ELITE INDUSTRIAL ESTATE OFF JALAN BUKIT KEMUNING 40000 SHAH ALAM PH: (603) 5122 2522 FAX: (603) 5122 2526

"The information contained in this technical publication is based on our current knowledge and experience and is provided as a guide only. In view of the many factors that may affect application it is the users sole responsibility to ensure suitability for a specific purpose."