

PREMIXED FLEXIBLE ACRYLIC ADHESIVE

PACKAGING



MIXING




APPLICATION



WALLS—6mm Notch

USES



SUBSTRATES

GYPSUM BUILDING
BOARD
CEMENT SHEET
PLYWOOD
CEMENT RENDER
BRICK, BLOCK
CONCRETE

DESCRIPTION

SUREFIX is a white premixed, economical, thin bed acrylic based ceramic tile adhesive.

USES

Fixing ceramic and mosaic tiles to clean and firm walls of plaster, gyprock, cement sheeting, cement render in kitchens, bathrooms and laundries.

Do not use between two non porous surfaces as the adhesive will not set. Not suitable for immersed applications, Construction Chemicals provide other systems.

COVERAGE (Approximate)

2kg per m².

PERFORMANCE DATA

Exceeds the performance requirements of AS4992

SPECIFICATION

The ceramic tile adhesive shall be a premixed flexible acrylic adhesive that exceeds the requirements of AS4992 and has a minimum shear bond strength of 2.49Mpa such as SUREFIX manufactured by Construction Chemicals and shall be applied in accordance with the manufacturers application instruction.

SURFACE PREPARATION

Surfaces must be structurally sound, free from dirt, dust, grease, and other contaminants. Cement render must be 7 days old. Building boards must be firmly fixed at 450 mm centres to restrain movement with rough side out where possible. Remove paint and prime highly absorbent surfaces (i.e. cement sheeting) with PRIMER & GROUT ADDITIVE and allow to dry before application of adhesive.

APPLICATION

Apply the SUREFIX with a 6mm x 6mm notched trowel. Spread only 1 m² at a time as the adhesive dries rapidly.

Immediately press dry tiles into the ribs of adhesive ensuring that all of the tile is in contact with the adhesive before it dries. Remove any excess adhesive from the surface of the tile before it dries using a damp cloth. The adhesive bed should not be less than 1.6mm or greater than 3 mm thick.

COVERAGE

2kg per m² (approximately).

GROUTING

Allow 24 hours before commencing, longer in cold damp conditions or when using dense tiles. Use PRIMER & GROUT ADDITIVE or FLEXIBLE GROUT ADDITIVE with KEMGROUT.

SHELF LIFE 2 years

**CONSTRUCTION
CHEMICALS**

● **ADELAIDE** 467 - 469 SOUTH RD REGENCY PARK 5010 PH: (08) 8346 8013 FAX: (08) 8340 2052
 ● **BRISBANE** 45 COULSON ST WACOL 4076 PH: (07) 3271 2944 FAX: (07) 3271 3892
 ● **MELBOURNE** 11 GABRIELLE CT BAYSWATER NORTH 3153 PH: (03) 9761 4711 FAX: (03) 9761 4748
 ● **PERTH** 11 COLLIE RD WELSHPOOL 6106 PH: (08) 9356 9999 FAX: (08) 9356 9955
 ● **SYDNEY** 31 NEWTON RD WETHERILL PARK 2164 PH: (02) 9756 3533 FAX: (02) 9756 3534
 ● **AUCKLAND** 16 CARPENTER RD EAST TAMAKI PH: (09) 273 5444 FAX: 0800 266 236
 ● **KUALA LUMPUR** LOT 2 JALAN KECABI 33/2 ELITE INDUSTRIAL ESTATE OFF JALAN BUKIT KEMUNING
 40000 SHAH ALAM PH: (603) 5122 2522 FAX: (603) 5122 2526

"The information contained in this technical publication is based on our current knowledge and experience and is provided as a guide only. In view of the many factors that may affect application it is the users sole responsibility to ensure suitability for a specific purpose."