

PREMIXED FLEXIBLE ACRYLIC ADHESIVE

PACKAGING



MIXING




APPLICATION



WALLS—6mm Notch

USES



SUBSTRATES

GYPSUM BUILDING
BOARD
CEMENT SHEET
PLYWOOD
CEMENT RENDER
BRICK, BLOCK
CONCRETE

DESCRIPTION

A premixed flexible rubber based ceramic tile adhesive for internal and external areas subject to movement caused by vibration and temperature movement.

USES

Apply to clean and firm walls of plaster, gyprock, cement sheeting, cement render and porous concrete floors in kitchens, bathrooms, laundries, shower alcoves, external floors and walls.

Do not use the adhesive between two impervious surfaces as the adhesive will not set.

COVERAGE (Approximate)

0.8m² per litre.

PERFORMANCE DATA

Exceeds the performance requirements of AS2358 and BS5385

Shear Bond Strength 1.24Mpa

SPECIFICATION

The ceramic tile adhesive will be a one pack flexible acrylic paste adhesive that conforms with AS2358 and BS5385 and has a minimum shear bond strength of 1.24Mpa such as SUREFLEX manufactured by Construction Chemicals and shall be applied in accordance with the manufacturers application instruction.

SURFACE PREPARATION

All surfaces must be sound, firm and free from oil, grease, dust and other contaminants. Prime porous surfaces with PRIMER AND GROUT ADDITIVE.

APPLICATION

Stir adhesive to ensure uniformity. Apply SUREFLEX with a 6mm x 6mm notched trowel for walls and 10mm x 10mm notched trowel for floors. Spread only 1 m² at a time as the adhesive dries rapidly. Immediately press dry tiles into the ribs of the adhesive ensuring that all of the tile is in contact with the adhesive before it dries. Irregular backed tiles should be buttered before applying to the adhesive ribs to ensure complete adhesion. The adhesive bed must be not less than 3mm to accommodate movement. Remove excess adhesive from the surface of the tile before it dries, using a damp cloth. Adjustments can be made to the tile for up to 20 minutes.

GROUTING

Allow adhesive to cure for 24 hours before grouting with KEMGROUT mixed with PRIMER AND GROUT ADDITIVE.

SHELF LIFE

2 years

**CONSTRUCTION
CHEMICALS**

1ADELAIDE 467 - 469 SOUTH RD REGENCY PARK 5010 PH: (08) 8346 8013 FAX: (08) 8340 2052
1BRISBANE 45 COULSON ST WACOL 4076 PH: (07) 3271 2944 FAX: (07) 3271 3892
1MELBOURNE 11 GABRIELLE CT BAYSWATER NORTH 3153 PH: (03) 9761 4711 FAX: (03) 9761 4748
1PERTH 11 COLLIE RD WELSHPOOL 6106 PH: (08) 9356 9999 FAX: (08) 9356 9955
1SYDNEY 31 NEWTON RD WETHERILL PARK 2164 PH: (02) 9756 3533 FAX: (02) 9756 3534
1AUCKLAND 16 CARPENTER RD EAST TAMAKI PH: (09) 273 5444 FAX: 0800 266 236
1KUALA LUMPUR LOT 2 JALAN KECAPI 33/2 ELITE INDUSTRIAL ESTATE OFF JALAN BUKIT KEMUNING
40000 SHAH ALAM PH: (603) 5122 2522 FAX: (603) 5122 2526

"The information contained in this technical publication is based on our current knowledge and experience and is provided as a guide only. In view of the many factors that may affect application it is the users sole responsibility to ensure suitability for a specific purpose."