

## CLEAR INTERIOR SEALER FOR TERRACOTTA AND POROUS SURFACES

## PACKAGING



## MIXING



## APPLICATION



## USES



## SUBSTRATES

POROUS,  
NATURAL STONE,  
SANDSTONE,  
QUARRY TILES  
SLATE & TERRACOTTA

**DESCRIPTION**

**Terra Guard** is a blend of acrylic, wax and stain repellent polymers which provides an easily maintained sealer for porous surfaces especially when used in conjunction with **Prime Seal**.

**USES**

For sealing interior porous surfaces such as terracotta, quarry tiles, sandstone and other porous tiles. **Not suitable for external use.**

**FEATURES**

- Available in Matt or Gloss
- Minimal Surface change
- Suitable for high speed polishing
- Simple to apply
- Easily maintained
- Resists staining
- Water based

**COVERAGE** (approximate)

Approx. 10-12m<sup>2</sup>/L/coat. 2-3 coats required.

**SPECIFICATION**

The coating shall be a water based wax/acrylic blend such as Terraguard manufactured by Construction Chemicals and shall be applied in accordance with the manufacturer's instructions.

**SURFACE PREPARATION**

Make sure surface is clean dry and has no previous sealer. Pre-seal porous surfaces with **Prime Seal** (see packaging for details). **Always apply to a test area before commencing to ensure suitability. Prime Seal not required for slate. Shake well before use.**

**APPLICATION**

Terra Guard can be applied easily with a lambswool applicator or brush. Apply one coat taking care to avoid puddling. After approximately 2 hours apply a second coat or for best results a third coat. Allow to cure for 24 hours before putting into use. A regular maintenance coat can be reapplied at regular intervals depending on wear. (ie 2 capfuls per 10 L of water). For a higher gloss the product can be machine buffed. If coating builds up in certain areas over time, **Terra Guard** can be completely removed using an ammonia based cleaner or cloudy ammonia. **Do not use ammonia based cleaners for regular mopping.** Stain resistance should be tested with substances common to the area. Allow grout to cure a minimum of 48 hours.

**SAFETY**

Avoid contact with skin and eyes. Keep out of the reach of children.

**FIRST AID**

If swallowed contact a doctor. Do not induce vomiting. If in eyes flood with water for about 15 minutes and seek medical advice.

**SHELF LIFE**

2 Years.

**CONSTRUCTION  
CHEMICALS**

1:ADELAIDE 467 - 469 SOUTH RD REGENCY PARK 5010 PH: (08) 8346 8013 FAX: (08) 8340 2052  
 1:BRISBANE 45 COULSON ST WACOL 4076 PH: (07) 3271 2944 FAX: (07) 3271 3892  
 1:MELBOURNE 11 GABRIELLE CT BAYSWATER NORTH 3153 PH: (03) 9761 4711 FAX: (03) 9761 4748  
 1:PERTH 11 COLLIE RD WELSHPOOL 6106 PH: (08) 9356 9999 FAX: (08) 9356 9955  
 1:SYDNEY 31 NEWTON RD WETHERILL PARK 2164 PH: (02) 9756 3533 FAX: (02) 9756 3534  
 1:AUCKLAND 16 CARPENTER RD EAST TAMAKI PH: (09) 273 5444 FAX: 0800 266 236  
 1:KUALA LUMPUR LOT 2 JALAN KECAPI 33/2 ELITE INDUSTRIAL ESTATE OFF JALAN BUKIT KEMUNING  
 40000 SHAH ALAM PH: (603) 5122 2522 FAX: (603) 5122 2526

"The information contained in this technical publication is based on our current knowledge and experience and is provided as a guide only. In view of the many factors that may affect application it is the users sole responsibility to ensure suitability for a specific purpose."