

MAPEI PLANICRETE

Chemwatch Material Safety Data Sheet
Issue Date: Fri 1-Apr-2005

CHEMWATCH 5046-26
CD 2005/3 Page 1 of 10

Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME

MAPEI PLANICRETE

SYNONYMS

"synthetic latex dispersion"

PRODUCT USE

Synthetic resin latex.

SUPPLIER

Company: Mapei Australia P/L

Address:

12 Parkview Drive

Archerfield

QLD, 4108

AUS

Telephone: +61 7 3276 5000

Fax: +61 7 3276 5076

Section 2 - HAZARDS IDENTIFICATION

STATEMENT OF HAZARDOUS NATURE

NON-HAZARDOUS SUBSTANCE. NON-DANGEROUS GOODS. According to the Criteria of NOHSC, and the ADG Code.

POISONS SCHEDULE

None

RISK

Ingestion may produce health damage*.

May produce discomfort of the eyes and skin*.

* (limited evidence).

SAFETY

Do not breathe gas/fumes/vapour/spray.

Wear eye/face protection.

Take off immediately all contaminated clothing.

In case of contact with eyes, rinse with plenty of water and contact Doctor or Poisons Information Centre.

If you feel unwell contact Doctor or Poisons Information Centre. (Show the label if possible).

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

NAME	CAS RN	%
polymer dispersion		10-60
calcium chloride	10043-52-4	<5
water	7732-18-5	30-60

continued...

MAPEI PLANICRETE

Chemwatch Material Safety Data Sheet
Issue Date: Fri 1-Apr-2005

CHEMWATCH 5046-26
CD 2005/3 Page 2 of 10

Section 4 - FIRST AID MEASURES

SWALLOWED

- For advice, contact a Poisons Information Centre or a doctor at once.
- Urgent hospital treatment is likely to be needed.
- If swallowed do NOT induce vomiting.
- If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.
- Observe the patient carefully.
- Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious.
- Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink.
- Transport to hospital or doctor without delay.

EYE

If this product comes in contact with the eyes:

- Wash out immediately with fresh running water.
- Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.
- If pain persists or recurs seek medical attention.
- Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

SKIN

If skin contact occurs:

- Immediately remove all contaminated clothing, including footwear
- Flush skin and hair with running water (and soap if available).
- Seek medical attention in event of irritation.

INHALED

- If fumes or combustion products are inhaled remove from contaminated area.
- Other measures are usually unnecessary.

NOTES TO PHYSICIAN

Treat symptomatically.

Section 5 - FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA

- There is no restriction on the type of extinguisher which may be used.
- Use extinguishing media suitable for surrounding area.

FIRE FIGHTING

- Alert Fire Brigade and tell them location and nature of hazard.
- Wear breathing apparatus plus protective gloves for fire only.
- Prevent, by any means available, spillage from entering drains or water courses.
- Use fire fighting procedures suitable for surrounding area.
- DO NOT approach containers suspected to be hot.
- Cool fire exposed containers with water spray from a protected location.
- If safe to do so, remove containers from path of fire.
- Equipment should be thoroughly decontaminated after use.

FIRE/EXPLOSION HAZARD

- Non combustible.
- Not considered to be a significant fire risk.

continued...

MAPEI PLANICRETE

Chemwatch Material Safety Data Sheet
Issue Date: Fri 1-Apr-2005

CHEMWATCH 5046-26
CD 2005/3 Page 3 of 10
Section 5 - FIRE FIGHTING MEASURES

- Expansion or decomposition on heating may lead to violent rupture of containers.
- Decomposes on heating and may produce toxic/ irritating fumes.
- May emit acrid smoke.

FIRE INCOMPATIBILITY

None known.

HAZCHEM

None

Personal Protective Equipment

PERSONAL PROTECTION EQUIPMENT

Gloves, boots (chemical resistant).

Section 6 - ACCIDENTAL RELEASE MEASURES

EMERGENCY PROCEDURES

MINOR SPILLS

- Clean up all spills immediately.
- Avoid breathing vapours and contact with skin and eyes.
- Control personal contact by using protective equipment.
- Contain and absorb spill with sand, earth, inert material or vermiculite.
- Wipe up.
- Place in a suitable labelled container for waste disposal.

MAJOR SPILLS

Moderate hazard.

- Clear area of personnel and move upwind.
- Alert Fire Brigade and tell them location and nature of hazard.
- Wear breathing apparatus plus protective gloves.
- Prevent, by any means available, spillage from entering drains or water course.
- Stop leak if safe to do so.
- Contain spill with sand, earth or vermiculite.
- Collect recoverable product into labelled containers for recycling.
- Neutralise/decontaminate residue.
- Collect solid residues and seal in labelled drums for disposal.
- Wash area and prevent runoff into drains.
- After clean up operations, decontaminate and launder all protective clothing and equipment before storing and re-using.
- If contamination of drains or waterways occurs, advise emergency services.

EMERGENCY RESPONSE PLANNING GUIDELINES (ERPG)

The maximum airborne concentration below which it is believed that nearly all individuals could be exposed for up to one hour WITHOUT experiencing or developing

life-threatening health effects is:

calcium chloride	400 mg/m ³
water	500 mg/m ³

irreversible or other serious effects or symptoms which could impair an individual's ability to take protective action is:

calcium chloride	20 mg/m ³
water	500 mg/m ³

other than mild, transient adverse effects

continued...

MAPEI PLANICRETE

Chemwatch Material Safety Data Sheet
Issue Date: Fri 1-Apr-2005

CHEMWATCH 5046-26
CD 2005/3 Page 4 of 10

Section 6 - ACCIDENTAL RELEASE MEASURES

without perceiving a clearly defined odour is:

calcium chloride	3.5 mg/m ³
water	500 mg/m ³

The threshold concentration below which most people will experience no appreciable risk of health effects:

calcium chloride	1 mg/m ³
water	500 mg/m ³

American Industrial Hygiene Association (AIHA)

Ingredients considered according exceed the following cutoffs

Very Toxic (T+) >= 0.1%	Toxic (T)	>= 3.0%
R50 >= 0.25%	Corrosive (C)	>= 5.0%
R51 >= 2.5%		
else >= 10%		

where percentage is percentage of ingredient found in the mixture

Personal Protective Equipment advice is contained in Section 8 of the MSDS.

Section 7 - HANDLING AND STORAGE

PROCEDURE FOR HANDLING

- Avoid all personal contact, including inhalation.
 - Wear protective clothing when risk of exposure occurs.
 - Use in a well-ventilated area.
 - Avoid contact with moisture.
 - Avoid contact with incompatible materials.
 - When handling, DO NOT eat, drink or smoke.
 - Keep containers securely sealed when not in use.
 - Avoid physical damage to containers.
 - Always wash hands with soap and water after handling.
 - Work clothes should be laundered separately. Launder contaminated clothing before re-use.
 - Use good occupational work practice.
 - Observe manufacturer's storing and handling recommendations.
 - Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained.
- DO NOT allow clothing wet with material to stay in contact with skin.

SUITABLE CONTAINER

- Polyethylene or polypropylene container.
- Packing as recommended by manufacturer
- Check all containers are clearly labelled and free from leaks.

STORAGE INCOMPATIBILITY

None known.

STORAGE REQUIREMENTS

- Store in original containers.
- Keep containers securely sealed.
- Store in a cool, dry, well-ventilated area.
- Store away from incompatible materials and foodstuff containers.
- Protect containers against physical damage and check regularly for leaks.
- Observe manufacturer's storing and handling recommendations.

continued...

MAPEI PLANICRETE

Chemwatch Material Safety Data Sheet
Issue Date: Fri 1-Apr-2005

CHEMWATCH 5046-26
CD 2005/3 Page 5 of 10

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE CONTROLS

No data available for calcium chloride as (CAS: 10043-52-4)

No data available for water as (CAS: 7732-18-5)

Not available. Refer to individual constituents.

EXPOSURE STANDARDS FOR MIXTURE

"Worst Case" computer-aided prediction of spray/ mist or fume/ dust components and concentration:

"Worst Case" computer-aided prediction of spray/ mist or fume/ dust components and concentration:

Composite Exposure Standard for Mixture (TWA) :10 mg/m³.

"Worst Case" computer-aided prediction of spray/ mist or fume/ dust components and concentration:

Composite Exposure Standard for Mixture (TWA) (mg/m³):

Operations which produce a spray/mist or fume/dust, introduce particulates to the breathing zone.

If the breathing zone concentration of ANY of the components listed below is exceeded, "Worst Case" considerations deem the individual to be overexposed.

Component Breathing Zone ppm Breathing Zone mg/m³ Mixture Conc (%)

Component	Breathing Zone (mg/m ³)	Mixture Conc (%)
calcium chloride	10.0000	5.0

INGREDIENT DATA

CALCIUM CHLORIDE:

Dusts not otherwise classified, as inspirable dust;

ES TWA: 10 mg/m³.

WATER:

No exposure limits set by NOHSC or ACGIH.

PERSONAL PROTECTION

EYE

- Safety glasses with side shields.
- Chemical goggles.
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lens or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59].

HANDS/FEET

Wear chemical protective gloves, eg. PVC.

Wear safety footwear or safety gumboots, eg. Rubber.

OTHER

- Overalls.
- P.V.C. apron.

continued...

MAPEI PLANICRETE

Chemwatch Material Safety Data Sheet
Issue Date: Fri 1-Apr-2005

CHEMWATCH 5046-26
CD 2005/3 Page 6 of 10

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

- Barrier cream.
- Skin cleansing cream.
- Eye wash unit.

GLOVE SELECTION INDEX

Glove selection is based on a modified presentation of the:
"Forsberg Clothing Performance Index".

The effect(s) of the following substance(s) are taken into account in the computer-generated selection: water

Glove selection is based on a modified presentation of the:
"Forsberg Clothing Performance Index".

The effect(s) of the following substance(s) are taken into account in the computer-generated selection:

Protective Material CPI *

BUTYL	A
NEOPRENE	A
VITON	A
PVA	C
NATURAL RUBBER	C

Glove selection is based on a modified presentation of the:
"Forsberg Clothing Performance Index".

The effect(s) of the following substance(s) are taken into account in the computer-generated selection:

Protective Material CPI *

* CPI - Chemwatch Performance Index

A: Best Selection

B: Satisfactory; may degrade after 4 hours continuous immersion

C: Poor to Dangerous Choice for other than short term immersion

NOTE: As a series of factors will influence the actual performance of the glove, a final selection must be based on detailed observation. -

* Where the glove is to be used on a short term, casual or infrequent basis, factors such as "feel" or convenience (e.g. disposability), may dictate a choice of gloves which might otherwise be unsuitable following long-term or frequent use. A qualified practitioner should be consulted.

RESPIRATOR

Selection of the Class and Type of respirator will depend upon the level of breathing zone contaminant and the chemical nature of the contaminant.

Protection Factors (defined as the ratio of contaminant outside and inside the mask) may also be important.

Breathing Zone Level ppm (volume)	Maximum Protection Factor	Half-face Respirator	Full-Face Respirator
1000	10	-AUS P	-
1000	50	-	-AUS P
5000	50	Airline *	-
5000	100	-	-2 P
10000	100	-	-3 P
	100+		Airline**

* - Continuous Flow ** - Continuous-flow or positive pressure demand.

The local concentration of material, quantity and conditions of use determine the type of personal protective equipment required.

For further information consult site specific CHEMWATCH data (if available), or your Occupational Health and Safety Advisor.

continued...

MAPEI PLANICRETE

Chemwatch Material Safety Data Sheet
Issue Date: Fri 1-Apr-2005

CHEMWATCH 5046-26
CD 2005/3 Page 7 of 10

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

ENGINEERING CONTROLS

General exhaust is adequate under normal operating conditions. Local exhaust ventilation may be required in specific circumstances. If risk of overexposure exists, wear approved respirator. Correct fit is essential to obtain adequate protection. Provide adequate ventilation in warehouse or closed storage areas. Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to effectively remove the contaminant.

Type of Contaminant: solvent, vapours, degreasing etc., evaporating from tank (in still air). aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation)	Air Speed: 0.25-0.5 m/s (50-100 f/min) 0.5-1 m/s (100-200 f/min.)
direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)	1-2.5 m/s (200-500 f/min.)
grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of very high rapid air motion).	2.5-10 m/s (500-2000 f/min.)

Within each range the appropriate value depends on:

Lower end of the range	Upper end of the range
1: Room air currents minimal or favourable to capture	1: Disturbing room air currents
2: Contaminants of low toxicity or of nuisance value only.	2: Contaminants of high toxicity
3: Intermittent, low production.	3: High production, heavy use
4: Large hood or large air mass in motion	4: Small hood-local control only

Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 1-2 m/s (200-400 f/min) for extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE

White liquid with a typical odour; disperses in water.

continued...

MAPEI PLANICRETE

Chemwatch Material Safety Data Sheet
Issue Date: Fri 1-Apr-2005

CHEMWATCH 5046-26
CD 2005/3 Page 8 of 10

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL PROPERTIES

Liquid.

Molecular Weight: Not applicable
Melting Range (°C): Not available
Solubility in water (g/L): dispersable
pH (1% solution): Not available
Volatile Component (%vol): Not available
Relative Vapour Density (air=1): Not available
Lower Explosive Limit (%): Not available
Autoignition Temp (°C): Not available
State: Liquid

Boiling Range (°C): 100
Specific Gravity (water=1): 1.01
pH (as supplied): 10
Vapour Pressure (kPa): Not available
Evaporation Rate: Not available
Flash Point (°C): Not available
Upper Explosive Limit (%): Not available
Decomposition Temp (°C): Not available

Section 10 - CHEMICAL STABILITY AND REACTIVITY INFORMATION

CONDITIONS CONTRIBUTING TO INSTABILITY

- Presence of incompatible materials.
- Product is considered stable.
- Hazardous polymerisation will not occur.

Section 11 - TOXICOLOGICAL INFORMATION

POTENTIAL HEALTH EFFECTS

ACUTE HEALTH EFFECTS

SWALLOWED

Accidental ingestion of the material may be damaging to the health of the individual.

EYE

There is some evidence to suggest that this material can cause eye irritation and damage in some persons.

SKIN

There is some evidence to suggest that this material can cause inflammation of the skin on contact in some persons.

Skin contact is not thought to have harmful health effects (as classified under EC Directives); the material may still produce health damage following entry through wounds, lesions or abrasions.

Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.

The material may cause skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin.

INHALED

The material is not thought to produce either adverse health effects or irritation of the respiratory tract following inhalation (as classified by EC Directives using animal models). Nevertheless, adverse systemic effects have been produced following exposure of animals by at least one other route and good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting.

continued...

MAPEI PLANICRETE

Chemwatch Material Safety Data Sheet
Issue Date: Fri 1-Apr-2005

CHEMWATCH 5046-26
CD 2005/3 Page 9 of 10

Section 11 - TOXICOLOGICAL INFORMATION

CHRONIC HEALTH EFFECTS

Long-term exposure to the product is not thought to produce chronic effects adverse to the health (as classified by EC Directives using animal models); nevertheless exposure by all routes should be minimised as a matter of course.

TOXICITY AND IRRITATION

Not available. Refer to individual constituents.

unless otherwise specified data extracted from RTECS - Register of Toxic Effects of Chemical Substances

CALCIUM CHLORIDE:

TOXICITY

Oral (rat) LD50: 1000 mg/kg

Eye (unknown): severe*

IRRITATION

Skin (unknown): Moderate*

[IC]

WATER:

No significant acute toxicological data identified in literature search.

Section 12 - ECOLOGICAL INFORMATION

DO NOT discharge into sewer or waterways.

Refer to data for ingredients, which follows:

CALCIUM CHLORIDE:

Fish LC50 (96hr.) (mg/l): 8.4 (24hr)

Section 13 - DISPOSAL CONSIDERATIONS

- Recycle wherever possible.
 - Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified.
 - Dispose of by: Burial in a licenced land-fill or Incineration in a licenced apparatus (after admixture with suitable combustible material)
 - Decontaminate empty containers. Observe all label safeguards until containers are cleaned and destroyed.
- Puncture containers to prevent re-use and bury at an authorised landfill.

Section 14 - TRANSPORTATION INFORMATION

Dangerous Goods Class: None

Subrisk: None

UN/NA Number: None

Packing Group: None

Labels Required:

Additional Shipping Information:

International Transport Regulations:

IMO Dangerous Goods class: None

IMO Packing group: None

IATA Dangerous goods class: None

Cargo Instructions:

Cargo Max:

Passenger Instructions:

Passenger Max:

Special Provisions: None, None

continued...

MAPEI PLANICRETE

Chemwatch Material Safety Data Sheet
Issue Date: Fri 1-Apr-2005

CHEMWATCH 5046-26
CD 2005/3 Page 10 of 10

Section 14 - TRANSPORTATION INFORMATION

HAZCHEM

None

Section 15 - REGULATORY INFORMATION

POISONS SCHEDULE

None

REGULATIONS

calcium chloride (CAS: 10043-52-4) is found on the following regulatory lists:
Australian Inventory of Chemical Substances (AICS)
Australia High Volume Industrial Chemical List (HVICL)

water (CAS: 7732-18-5) is found on the following regulatory lists:
Australian Inventory of Chemical Substances (AICS)

Section 16 - OTHER INFORMATION

This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.

Issue Date: Fri 1-Apr-2005
Print Date: Tue 15-Nov-2005