

MAPEI ULTRA/BOND ECO 8200

Chemwatch Material Safety Data Sheet
Issue Date: Fri 1-Apr-2005

CHEMWATCH 5075-05
CD 2005/3 Page 1 of 8

Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME

MAPEI ULTRA/BOND ECO 8200

SYNONYMS

"synthetic polymer based water borne adhesive acrylic based carpet adhesive",
"misspelling marpay as"

PRODUCT USE

Acrylic-based universal carpet seam adhesive.

SUPPLIER

Company: Mapei Australia P/L
Address:
12 Parkview Drive
Archerfield
QLD, 4108
AUS
Telephone: +61 7 3276 5000
Fax: +61 7 3276 5076

Section 2 - HAZARDS IDENTIFICATION

STATEMENT OF HAZARDOUS NATURE

NON-HAZARDOUS SUBSTANCE. NON-DANGEROUS GOODS. According to the Criteria of NOHSC, and the ADG Code.

POISONS SCHEDULE

None

RISK

May produce discomfort of the eyes and skin*.
* (limited evidence).

SAFETY

Avoid contact with skin.
Wear eye/face protection.
In case of contact with eyes, rinse with plenty of water and contact Doctor or Poisons Information Centre.

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

NAME	CAS RN	%
adhesive base as acrylic resin fillers unspecified.	Various	Not spec.
water	7732-18-5	Not spec.
No other ingredient information supplied.		

continued...

MAPEI ULTRA/BOND ECO 8200

Chemwatch Material Safety Data Sheet
Issue Date: Fri 1-Apr-2005

CHEMWATCH 5075-05
CD 2005/3 Page 2 of 8

Section 4 - FIRST AID MEASURES

SWALLOWED

- Immediately give a glass of water.
- First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.

EYE

If this product comes in contact with the eyes:

- Wash out immediately with fresh running water.
- Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.
- If pain persists or recurs seek medical attention.
- Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

SKIN

If skin contact occurs:

- Immediately remove all contaminated clothing, including footwear
- Flush skin and hair with running water (and soap if available).
- Seek medical attention in event of irritation.

INHALED

- If fumes or combustion products are inhaled remove from contaminated area.
- Other measures are usually unnecessary.

NOTES TO PHYSICIAN

Treat symptomatically.

Section 5 - FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA

- There is no restriction on the type of extinguisher which may be used. Use extinguishing media suitable for surrounding area.

FIRE FIGHTING

- Alert Fire Brigade and tell them location and nature of hazard.
- Wear breathing apparatus plus protective gloves for fire only.
- Prevent, by any means available, spillage from entering drains or water courses.
- Use fire fighting procedures suitable for surrounding area.
- DO NOT approach containers suspected to be hot.
- Cool fire exposed containers with water spray from a protected location.
- If safe to do so, remove containers from path of fire.
- Equipment should be thoroughly decontaminated after use.

FIRE/EXPLOSION HAZARD

- Non combustible.
- Not considered a significant fire risk, however containers may burn.

FIRE INCOMPATIBILITY

None known.

HAZCHEM

None

continued...

MAPEI ULTRA/BOND ECO 8200

Chemwatch Material Safety Data Sheet
Issue Date: Fri 1-Apr-2005

CHEMWATCH 5075-05
CD 2005/3 Page 3 of 8
Section 5 - FIRE FIGHTING MEASURES

Personal Protective Equipment

PERSONAL PROTECTION EQUIPMENT
Gloves, boots (chemical resistant).

Section 6 - ACCIDENTAL RELEASE MEASURES

EMERGENCY PROCEDURES

MINOR SPILLS

- Clean up all spills immediately.
- Avoid breathing vapours and contact with skin and eyes.
- Control personal contact by using protective equipment.
- Contain and absorb spill with sand, earth, inert material or vermiculite.
- Wipe up.
- Place in a suitable labelled container for waste disposal.

MAJOR SPILLS

Moderate hazard.

- Clear area of personnel and move upwind.
- Alert Fire Brigade and tell them location and nature of hazard.
- Wear breathing apparatus plus protective gloves.
- Prevent, by any means available, spillage from entering drains or water course.
- Stop leak if safe to do so.
- Contain spill with sand, earth or vermiculite.
- Collect recoverable product into labelled containers for recycling.
- Neutralise/decontaminate residue.
- Collect solid residues and seal in labelled drums for disposal.
- Wash area and prevent runoff into drains.
- After clean up operations, decontaminate and launder all protective clothing and equipment before storing and re-using.
- If contamination of drains or waterways occurs, advise emergency services.

EMERGENCY RESPONSE PLANNING GUIDELINES (ERPG)

The maximum airborne concentration below which it is believed that nearly all individuals could be exposed for up to one hour WITHOUT experiencing or developing

life-threatening health effects is:

water 500 mg/m³

irreversible or other serious effects or symptoms which could impair an individual's ability to take protective action is:

water 500 mg/m³

other than mild, transient adverse effects without perceiving a clearly defined odour is:

water 500 mg/m³

The threshold concentration below which most people will experience no appreciable risk of health effects:

water 500 mg/m³

American Industrial Hygiene Association (AIHA)

Ingredients considered according exceed the following cutoffs

Very Toxic (T+) >= 0.1%	Toxic (T) >= 3.0%
R50 >= 0.25%	Corrosive (C) >= 5.0%
R51 >= 2.5%	

continued...

MAPEI ULTRA/BOND ECO 8200

Chemwatch Material Safety Data Sheet
Issue Date: Fri 1-Apr-2005

CHEMWATCH 5075-05
CD 2005/3 Page 4 of 8

Section 6 - ACCIDENTAL RELEASE MEASURES

else $\geq 10\%$
where percentage is percentage of ingredient found in the mixture

Personal Protective Equipment advice is contained in Section 8 of the MSDS.

Section 7 - HANDLING AND STORAGE

PROCEDURE FOR HANDLING

- Avoid all personal contact, including inhalation.
 - Wear protective clothing when risk of exposure occurs.
 - Use in a well-ventilated area.
 - Avoid contact with moisture.
 - Avoid contact with incompatible materials.
 - When handling, DO NOT eat, drink or smoke.
 - Keep containers securely sealed when not in use.
 - Avoid physical damage to containers.
 - Always wash hands with soap and water after handling.
 - Work clothes should be laundered separately. Launder contaminated clothing before re-use.
 - Use good occupational work practice.
 - Observe manufacturer's storing and handling recommendations.
 - Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained.
- DO NOT allow clothing wet with material to stay in contact with skin.

SUITABLE CONTAINER

- Polyethylene or polypropylene container.
- Packing as recommended by manufacturer
- Check all containers are clearly labelled and free from leaks.

STORAGE INCOMPATIBILITY

None known.

STORAGE REQUIREMENTS

- Store in original containers.
 - Keep containers securely sealed.
 - Store in a cool, dry, well-ventilated area.
 - Store away from incompatible materials and foodstuff containers.
 - Protect containers against physical damage and check regularly for leaks.
 - Observe manufacturer's storing and handling recommendations.
-

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE CONTROLS

No data available for acrylic resin as (CAS: Various)
No data available for water as (CAS: 7732-18-5)
None assigned for mixture or identified for ingredient(s).

INGREDIENT DATA

ACRYLIC RESIN:

Dusts not otherwise classified, as inspirable dust;
ES TWA: 10 mg/m³.

WATER:

No exposure limits set by NOHSC or ACGIH.

continued...

MAPEI ULTRA/BOND ECO 8200

Chemwatch Material Safety Data Sheet
Issue Date: Fri 1-Apr-2005

CHEMWATCH 5075-05
CD 2005/3 Page 5 of 8

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

PERSONAL PROTECTION

EYE

- Safety glasses with side shields.
- Chemical goggles.
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lens or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59].

HANDS/FEET

Wear chemical protective gloves, eg. PVC.
Wear safety footwear or safety gumboots, eg. Rubber.

OTHER

- Overalls.
- P.V.C. apron.
- Barrier cream.
- Skin cleansing cream.
- Eye wash unit.

The local concentration of material, quantity and conditions of use determine the type of personal protective equipment required. For further information consult site specific CHEMWATCH data (if available), or your Occupational Health and Safety Advisor.

ENGINEERING CONTROLS

General exhaust is adequate under normal operating conditions. Local exhaust ventilation may be required in specific circumstances. If risk of overexposure exists, wear approved respirator. Correct fit is essential to obtain adequate protection. Provide adequate ventilation in warehouse or closed storage areas. Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to effectively remove the contaminant.

Type of Contaminant: solvent, vapours, degreasing etc., evaporating from tank (in still air).	Air Speed: 0.25-0.5 m/s (50-100 f/min)
aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation)	0.5-1 m/s (100-200 f/min.)
direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)	1-2.5 m/s (200-500 f/min.)
grinding, abrasive blasting, tumbling,	2.5-10 m/s (500-2000 f/min.)

continued...

MAPEI ULTRA/BOND ECO 8200

Chemwatch Material Safety Data Sheet
Issue Date: Fri 1-Apr-2005

CHEMWATCH 5075-05
CD 2005/3 Page 6 of 8

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

high speed wheel generated dusts
(released at high initial velocity into
zone of very high rapid air motion).

Within each range the appropriate value depends on:

Lower end of the range

- 1: Room air currents minimal or favourable to capture
- 2: Contaminants of low toxicity or of nuisance value only.
- 3: Intermittent, low production.
- 4: Large hood or large air mass in motion

Upper end of the range

- 1: Disturbing room air currents
- 2: Contaminants of high toxicity
- 3: High production, heavy use
- 4: Small hood-local control only

Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 1-2 m/s (200-400 f/min) for extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE

Milky white with an acrylic odour; mixes with water.

PHYSICAL PROPERTIES

Liquid.
Mixes with water.

Molecular Weight: Not applicable
Melting Range (°C): Not available
Solubility in water (g/L): Miscible
pH (1% solution): Not available
Volatile Component (%vol): Not available
Relative Vapour Density (air=1): Not available
Lower Explosive Limit (%): Not applicable
Autoignition Temp (°C): Not applicable
State: Liquid

Boiling Range (°C): 100
Specific Gravity (water=1): 1.24
pH (as supplied): Not available
Vapour Pressure (kPa): Not available
Evaporation Rate: Not available
Flash Point (°C): Non Flammable
Upper Explosive Limit (%): Not applicable
Decomposition Temp (°C): Not available

Section 10 - CHEMICAL STABILITY AND REACTIVITY INFORMATION

CONDITIONS CONTRIBUTING TO INSTABILITY

- Presence of incompatible materials.
- Product is considered stable.
- Hazardous polymerisation will not occur.

continued...

MAPEI ULTRA/BOND ECO 8200

Chemwatch Material Safety Data Sheet
Issue Date: Fri 1-Apr-2005

CHEMWATCH 5075-05
CD 2005/3 Page 7 of 8

Section 11 - TOXICOLOGICAL INFORMATION

POTENTIAL HEALTH EFFECTS

ACUTE HEALTH EFFECTS

SWALLOWED

The material has NOT been classified by EC Directives or other classification systems as "harmful by ingestion". This is because of the lack of corroborating animal or human evidence. The material may still be damaging to the health of the individual, following ingestion, especially where pre-existing organ (eg. liver, kidney) damage is evident. Present definitions of harmful or toxic substances are generally based on doses producing mortality rather than those producing morbidity (disease, ill-health). Gastrointestinal tract discomfort may produce nausea and vomiting. In an occupational setting however, ingestion of insignificant quantities is not thought to be cause for concern.

EYE

There is some evidence to suggest that this material can cause eye irritation and damage in some persons.

SKIN

There is some evidence to suggest that this material can cause inflammation of the skin on contact in some persons.

Skin contact is not thought to have harmful health effects (as classified under EC Directives); the material may still produce health damage following entry through wounds, lesions or abrasions.

INHALED

The material is not thought to produce adverse health effects or irritation of the respiratory tract (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting.

CHRONIC HEALTH EFFECTS

Long-term exposure to the product is not thought to produce chronic effects adverse to the health (as classified by EC Directives using animal models); nevertheless exposure by all routes should be minimised as a matter of course.

TOXICITY AND IRRITATION

TOXICITY

Not available for mixture or identified for ingredient(s).

IRRITATION

ACRYLIC RESIN:

No data of toxicological significance identified in literature search.

CAUTION: The chronic health effects of acrylic monomers are under review.

Use good occupational work practices to avoid personal contact.

WATER:

No significant acute toxicological data identified in literature search.

Section 12 - ECOLOGICAL INFORMATION

DO NOT discharge into sewer or waterways.

continued...

MAPEI ULTRA/BOND ECO 8200

Chemwatch Material Safety Data Sheet
Issue Date: Fri 1-Apr-2005

CHEMWATCH 5075-05
CD 2005/3 Page 8 of 8

Section 13 - DISPOSAL CONSIDERATIONS

- Recycle wherever possible.
- Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified.
- Dispose of by: Burial in a licenced land-fill or Incineration in a licenced apparatus (after admixture with suitable combustible material)
- Decontaminate empty containers. Observe all label safeguards until containers are cleaned and destroyed.

Section 14 - TRANSPORTATION INFORMATION

Dangerous Goods Class: None
Subrisk: None
UN/NA Number: None
Packing Group: None
Labels Required:
Additional Shipping Information:
International Transport Regulations:
IMO Dangerous Goods class: None
IMO Packing group: None
IATA Dangerous goods class: None
Cargo Instructions:
Cargo Max:
Passenger Instructions:
Passenger Max:
Special Provisions: None, None

HAZCHEM

None

Section 15 - REGULATORY INFORMATION

POISONS SCHEDULE

None

REGULATIONS

water (CAS: 7732-18-5) is found on the following regulatory lists:
Australian Inventory of Chemical Substances (AICS)
Chinese Synonyms

No data available for acrylic resin as CAS: Various.

Section 16 - OTHER INFORMATION

This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.

Issue Date: Fri 1-Apr-2005
Print Date: Tue 15-Nov-2005