



SOLUTIONS FOR INDUSTRY

ATLAS TILE ADHESIVES



Uniprime

Characteristics:

- Uniprime is an acrylic based universal wall / floor primer for use prior to the application of RLA/Atlas Tile adhesives.
- Uniprime increases the adhesion of RLA/Atlas Tile adhesives onto the substrate.
- Uniprime must be used to prime all absorbent surfaces including, timber floors, concrete, fibre cement sheets etc before tiling.
- Uniprime can be used as a bonding agent to bond old concrete to new.

Preparation:

- Ensure all surfaces are sound, dry and free from excessive movement, oil, dust, grease, wax, curing compounds, release agents, paint and any other loose contaminating materials.
- For non-porous surfaces like existing tiles, sheet vinyl etc or contaminated surfaces, please consult your local RLA /Atlas office for information.

Application:

- When applying the primer onto floor surfaces it is recommended to firstly pour some primer in a section then spread the primer using a broom, brush or roller. Then continue this method of application until the entire area is primed. **Note:** This method of application ensures a thorough coat of the primer on the surface.
- Allow the primer to dry for approximately 5 minutes at 20°C prior to commencing tiling / waterproofing.

Clean Up:

- Excess primer, tools and other equipment can be cleaned up using water while the primer is still wet.

Coverage:

- The coverage of Uniprime will vary depending upon the substrate. As a guide it will cover approximately 8-10m² / L.

Packaging / Shelf Life:

- Uniprime is available in 20L, 5L, and 1L Pails.
- A pail of Uniprime, when stored in a cool, dry environment, and is stored above ground level, will have a shelf life of approximately 12 months.

Handy Tips:

- Do not apply Uniprime in temperatures above 40°C and below 5°C.
- For applications / situations not mentioned in this data sheet please contact your nearest RLA/Atlas office.
- Uniprime is classified as a non-hazardous product.
- For a full MSDS on this product please contact your nearest RLA/Atlas office.

Technical Data:

Properties	Results
Appearance	White liquid
Density	1.10 +/- 0.05
Drying Time @ 20°C	Approx. 30 minutes

The information supplied is to the best of our knowledge true and accurate. The actual application of the product is beyond the manufacturer's control. Any failure or damage caused by the incorrect usage of the product is not the responsibility of the manufacturer. The manufacturer insists that all workmanship must be carried out in accordance with AS 3958.1-1991. It is also the responsibility of the end user to ensure that the literature in their possession is the latest issue.

RLA POLYMERS PTY LTD
ACN 004 709 915

Victoria
215 Colchester Road, Kilsyth
Victoria 3137, Australia

PO Box 147, Kilsyth
Victoria 3137, Australia

Telephone (03) 9728 1644
Facsimile (03) 9728 6009 Email:
info@riapolymers.com.au

Queensland
25 Campbell Rd.
Yatala Q.D. 4207
Telephone (07) 3807 4022
Facsimile (07) 3807 4755

New South Wales
363 Wentworth Ave.
Pendle Hill NSW 2145
Telephone (02) 9636 7444
Facsimile (02) 9636 7688

New Zealand
68 Dalgely Drive, Manukau City
Auckland, New Zealand

PO Box 97-575, Manukau City
Auckland, New Zealand

Telephone (9) 268 0301
Facsimile (9) 268 0305

Malaysia
No 5, Lebuh Raya Pelat, Pandamaran
42000 Port Klang, Selangor D.H.
Telephone 03-31661039
Facsimile 03-31661037

 A British Vita Group Company



The information supplied is to the best of our knowledge true and accurate. The actual application of the product is beyond the manufacturer's control. Any failure or damage caused by the incorrect usage of the product is not the responsibility of the manufacturer. The manufacturer insists that all workmanship must be carried out in accordance with AS 3958.1-1991. It is also the responsibility of the end user to ensure that the literature in their possession is the latest issue.